

Listing of Claims:

1. (Cancelled)
2. (Currently amended) A valve assembly of claim 1 comprising:
a valve body defining a chamber with a controlled outlet;
a stop and a seat supported within the chamber of the valve body in
axial alignment with the controlled outlet;
a plunger reciprocably movable between the stop and the seat to open
and close the controlled outlet respectively; and
a solenoid assembly operable on the plunger to move the plunger
between the stop and the seat, said solenoid assembly having a spool supported
between a primary and secondary plate, said spool having an electromagnetic coil
wound thereon for receiving electrical current and producing magnetic flux, wherein
magnetic flux produced by said electrical coil flows in a primary magnetic flux flow
path about said electrical coil, said primary magnetic flux flow path extending from
said secondary plate through a sleeve, from said sleeve to said primary plate and
through said primary plate to said plunger to said stop, and through said stop back
through the secondary plate, wherein the solenoid assembly includes means for
providing a secondary bypass magnetic flux flow path for a portion of the magnetic
flux and wherein the means for providing the secondary magnetic flux flow path
includes a magnetic flux regulator to form a short cut loop to bypass the plunger.
3. (Original) The valve assembly of claim 2, wherein the magnetic flux regulator has a first end portion communicating with the primary plate and has another end portion spaced from the stop.
4. (Original) The valve assembly of claim 2, wherein the magnetic flux regulator is made of magnetic conductive material.
5. (Original) The valve assembly of claim 4, wherein the magnetic flux regulator is an annular member disposed within the spool.

6. (Original) The valve assembly of claim 3, wherein the spool has a center bore for receiving a portion of the stop therein, said stop having a conductive body with a reduced area adjacent said spool.

7. (Original) The valve assembly of claim ⁶ 7, wherein the stop includes a resilient insert molded into the reduced area of the conductive body.

8. (Original) A valve assembly comprising:
a valve body defining a chamber with a controlled outlet;
plunger reciprocally movable within the chamber to open and close the controlled outlet;
a solenoid assembly operable to move the plunger upon receipt of electrical current to produce a magnetic flux having a primary path through the plunger and a secondary path bypassing the plunger.

9. (Original) The valve assembly of claim 8 further comprising means for limiting the total amount of magnetic flux produced by the electrical current.

JBH
12-5-03,
periatly
phone call